

High Capacity Electronic Balances ESK

Specifications:

Model	ES500KX5	ES100KX1D	ES300KX2	ES300KX5	ES200KX2
Max.(Capacity)	500 kg	100 kg	300 kg	300 kg	200 kg
Readability(d)	5 g	1 g	2 g	5 g	2 g
Minimum Weight (U=1%, k=2), typical	50 g	10 g	20 g	50 g	20 g
Repeatability(±)	5 g	1 g	2 g	10 g	2 g
Linearity(±)	10 g	2 g	4 g	10 g	4 g
Sensitivity Drift	±2 ppm/°C				
Make	LT				
Calibration	Motorized External Calibration				
Class	Class II				
Display	LCD				
Response Time	3-5 Sec				
Pan Size(mm)	650 x 750 mm				
Tare Range	Full				
Operating Temperature	+10°C to +40°C				
Density	Function Available				
Unit	g,mg,oz,ct,lb,ozt,dwt				
Application Mode	PCS/Percent Weighing,Animal Weighing,Density,Totalizing,(Add)Weighing				
Baud Rate Options	1200,2400,4800,9600				
Interface	RS232C				
Power Supply	DC24V, AC 220V/50-60 Hz				
Dimension (LxWxH)	650×750×230 mm				
Gross Weight	260 kg				
MOQ	1 Set				
Customs Tariff Number	9027899090				

Note:

The measuring range and model can be customized according to user requirements.

Density Determination Kit for Solid Samples(Optional)

Standard Accessories: Main Instrument,Weighing Pan,Ring,Power Adaptor,Antivibration Pad,Test Certificate