



High Precision Electronic Balances JD-2

Specifications:

Model	JD6000-2	JD5000-2	JD4000-2	JD3000-2	JD2000-2	JD1000-2
Max.(Capacity)	6000 g	5000 g	4000 g	3000 g	2000 g	1000 g
Readability(d)	0.01 g(10 mg)					
Minimum Weight (U=1%, k=2), typical	0.1 g					
Repeatability(±)	0.01 g					
Linearity(±)	0.02 g					
Sensitivity Drift	±2 ppm/°C					
Min.(Capacity)	0.1 g					
Make	LT					
Calibration	Motorized External Calibration					
Class	Class II					
Display	LCD					
Response Time	3-5 Sec					
Pan Size(mm)	φ160 mm					
Tare Range	Full					
Operating Temperature	+10°C to +40°C					
Density	Function Available					
Unit	g,mg,oz,ct,lb,ozt,dwt					
Application Mode	PCS/Percent Weighing,Animal Weighing,Density,Totalizing,(Add)Weighing					
Baud Rate Options	1200,2400,4800,9600					
Interface	RS232C					
Power Supply	DC15V 1A PC≤20W/50-60 Hz					
Dimension (LxWxH)	335×205×100 mm					
Gross Weight	3.5 kg					
MOQ	1 Set					
Customs Tariff Number	9016001000					

Note:

The measuring range and model can be customized according to user requirements.
Density Determination Kit for Solid Samples(Optional)

Standard Accessories: Main Instrument,Weighing Pan,Ring,Power Adaptor,Antivibration Pad,Test Certificate