

Electronic Balances with Loadcell LD-2

Specifications:

Model	LD310-2	LD510-2	LD610-2	LD1000-2	LD2000-2
Max.(Capacity)	310 g	510 g	610 g	1000 g	2000 g
Readability(d)	0.01 g(10 mg)				
Minimum Weight (U=1%, k=2), typical	1 g				
Repeatability(±)	0.02 g				
Linearity(±)	0.04 g				
Sensitivity Drift	±2 ppm/°C				
Min.(Capacity)	1 g				
Transducer	<u>Strain gauge</u>				
Calibration	Motorized External Calibration				
Class	Class II				
Display	LCD				
Response Time	3-5 Sec				
Pan Size(mm)	φ120 mm				
Tare Range	Full				
Operating Temperature	+10°C to +40°C				
Density	Function Available				
Unit	g,mg,oz,ct,lb,ozt,dwt				
Application Mode	PCS/Percent Weighing,Totalizing,(Add)Weighing				
Baud Rate Options	1200,2400,4800,9600				
Interface	RS232C				
Power Supply	AC Adapter (Included) or 6 AA Batteries (Not included)				
Dimension (LxWxH)	275×230×85 mm				
Gross Weight	2.5 kg				
MOQ	1 Set				
Customs Tariff Number	9027899090				

Note:

Standard Accessories: Main Instrument,Weighing Pan,Ring,Power Adaptor,Antivibration Pad,Test Certificate