

Electronic Balances with Loadcell LD-1

Specifications:

Model	LD6100-1	LD5100-1	LD3100-1	LD2100-1	LD1100-1
Max.(Capacity)	6100 g	5100 g	3100 g	2100 g	1100 g
Readability(d)	0.1 g				
Minimum Weight (U=1%, k=2), typical	1 g				
Repeatability(±)	0.1 g				
Linearity(±)	0.2 g				
Sensitivity Drift	±2 ppm/°C				
Min.(Capacity)	1 g				
Make	LT				
Calibration	Motorized External Calibration				
Class	Class III				
Display	LCD				
Response Time	3-5 Sec				
Pan Size(mm)	160 x 160 x 8 mm				
Tare Range	Full				
Operating Temperature	+10°C to +40°C				
Density	Function Available				
Unit	g,mg,oz,ct,lb,ozt,dwt				
Application Mode	PCS/Percent Weighing,Totalizing,(Add)Weighing				
Baud Rate Options	1200,2400,4800,9600				
Interface	RS232C				
Power Supply	AC Adapter (Included) or 6 AA Batteries (Not included)				
Dimension (LxWxH)	275×230×85 mm				
Gross Weight	2.5 kg				
MOQ	1 Set				
Customs Tariff Number	9027899090				

Note:

Standard Accessories: Main Instrument,Weighing Pan,Ring,Power Adaptor,Antivibration Pad,Test Certificate